

TECHNICAL DATA

	F-TYPE Coupé	F-TYPE Convertible
ENGINE & TRANSMISSION		
Engine capacity (cc)	2,995	
Cylinders	V6 Supercharged	
Valves per cylinder	4; DOHC	
Bore/ stroke (mm)	84.5/ 89.0	
Compression ratio	10.5:1	
Fuel injection	150bar direct injection	
Power kW	250 @ 6,500rpm	
Torque Nm	450 @ 3,500-5,000rpm	
Transmission	8-speed Quickshift, [6-speed manual]	
Gear ratios (:1)		
1st	4.714 [4.110]	
2nd	3.143 [2.315]	
3rd	2.106 [1.542]	
4th	1.667 [1.179]	
5th	1.285 [1.000]	
6th	1.000 [0.846]	
7th	0.839 [-]	
8th	0.667 [-]	
Reverse	3.317 [3.727]	
Final Drive	3.15 [3.31]	
CHASSIS		
Front suspension	Double wishbone	
Rear suspension	Double wishbone	
Front brakes	Single-piston sliding caliper; 355mm ventilated discs	
Rear brakes	Single-piston sliding caliper; 325mm ventilated discs	
Steering	Rack-and-pinion; electromechanical	
DIMENSIONS		
Length (mm)	4,470	4,470
Width excl. mirrors (mm)	1,923	1,923
Height (mm)	1,311	1,308
Wheelbase (mm)	2,622	2,622
Track front/ rear (mm)	1,597/ 1,649	1,597/ 1,649
Kerbweight (kg)	From 1,577 [1,567]	From 1,597 [1,587]
Boot volume (litres)	315/ 407 with/ without parcel tray and without Space Saver Spare	196.2 without Space Saver Spare
Fuel tank (usable) litres	70	70
PERFORMANCE & FUEL ECONOMY		
0-100km/h (sec)	5.3 [5.7]	5.3 [5.7]
Top speed km/h	260	260
Fuel consumption litres/100km EU combined	8.4 [9.8]	8.4 [9.8]
CO ₂ emissions (g/km) EU combined	199 [234]	199 [234]

Manufacturer's figures; correct at time of going to press

TECHNICAL DATA

	F-TYPE S Coupé	F-TYPE S Convertible
ENGINE & TRANSMISSION		
Engine capacity (cc)	2,995	
Cylinders	V6 Supercharged	
Valves per cylinder	4; DOHC	
Bore/ stroke (mm)	84.5/ 89.0	
Compression ratio	10.5:1	
Fuel injection	150bar direct injection	
Power kW	280 @ 6,500rpm	
Torque Nm	460 @ 3,500-5,000rpm	
Transmission	8-speed Quickshift, [6-speed manual – Coupe only]	
Gear ratios (:1)		
1st	4.714 [4.110]	
2nd	3.143 [2.315]	
3rd	2.106 [1.542]	
4th	1.667 [1.179]	
5th	1.285 [1.000]	
6th	1.000 [0.846]	
7th	0.839 [-]	
8th	0.667 [-]	
Reverse	3.317 [3.727]	
Final Drive	3.31 [3.31]	
CHASSIS		
Front suspension	Double wishbone	
Rear suspension	Double wishbone	
Front brakes	Twin-piston sliding caliper; 380mm ventilated discs	
Rear brakes	Single-piston sliding caliper; 325mm ventilated discs	
Steering	Rack-and-pinion; electromechanical	
DIMENSIONS		
Length (mm)	4,470	4,470
Width excl. mirrors (mm)	1,923	1,923
Height (mm)	1,311	1,308
Wheelbase (mm)	2,622	2,622
Track front/ rear (mm)	1,597/ 1,649	1,597/ 1,649
Kerbweight (kg)	From 1,594 [1,584]	From 1,614 [1,604]
Boot volume (litres)	315/ 407 with/ without parcel tray and without Space Saver Spare	196.2 without Space Saver Spare
Fuel tank (usable) litres	70	70
PERFORMANCE & FUEL ECONOMY		
0-100km/h (sec)	4.9 [5.5]	4.9 [5.5]
Top speed km/h	275	275
Fuel consumption mpg (litres/100km) EU combined	8.6 [9.8]	8.6 [9.8]
CO ₂ emissions (g/km) EU combined	203 [234]	203 [234]

Manufacturer's figures; correct at time of going to press

Figures in square brackets refer to manual transmission

TECHNICAL DATA

	F-TYPE S AWD Coupé	
ENGINE & TRANSMISSION		
Engine capacity (cc)	2,995	
Cylinders	V6 Supercharged	
Valves per cylinder	4; DOHC	
Bore/ stroke (mm)	84.5/ 89.0	
Compression ratio	10.5:1	
Fuel injection	150bar direct injection	
Power kW	280 @ 6,500rpm	
Torque Nm	460 @ 3,500-5,000rpm	
Transmission	8-speed Quickshift	
Gear ratios (:1)		
1st	4.714	
2nd	3.143	
3rd	2.106	
4th	1.667	
5th	1.285	
6th	1.000	
7th	0.839	
8th	0.667	
Reverse	3.317	
Final Drive	3.31	
CHASSIS		
Front suspension	Double wishbone	
Rear suspension	Double wishbone	
Front brakes	Twin-piston sliding caliper; 380mm ventilated discs	
Rear brakes	Single-piston sliding caliper; 325mm ventilated discs	
Steering	Rack-and-pinion; electromechanical	
DIMENSIONS		
Length (mm)	4,470	
Width excl. mirrors (mm)	1,923	
Height (mm)	1,311	
Wheelbase (mm)	2,622	
Track front/ rear (mm)	1,597/ 1,649	
Kerbweight (kg)	From 1,674	
Boot volume (litres)*	315/ 407 with/ without parcel tray and without Space Saver Spare	
Fuel tank (usable) litres	70	
PERFORMANCE & FUEL ECONOMY		
0-100km/h (sec)	5.1	
Top speed km/h	275	
Fuel consumption litres/100km EU combined	8.9	
CO ₂ emissions (g/km) EU combined	211	

Manufacturer's figures; correct at time of going to press

Figures in square brackets refer to manual transmission

TECHNICAL DATA

	F-TYPE R Coupé	F-TYPE R Convertible
ENGINE & TRANSMISSION		
Engine capacity (cc)	5,000	
Cylinders	V8 Supercharged	
Valves per cylinder	4; DOHC	
Bore/ stroke (mm)	92.5/ 93.0	
Compression ratio	9.5:1	
Fuel injection	150bar direct injection	
Power kW	404 @ 6,500rpm	
Torque Nm	680 @ 3,500rpm	
Transmission	8-speed Quickshift	
Gear ratios (:1)		
1st	4.714	
2nd	3.143	
3rd	2.106	
4th	1.667	
5th	1.285	
6th	1.000	
7th	0.839	
8th	0.667	
Reverse	3.317	
Final Drive	2.56	
CHASSIS		
Front suspension	Double wishbone	
Rear suspension	Double wishbone	
Front brakes	Twin-piston sliding caliper; 380mm ventilated discs	
Rear brakes	Single-piston sliding caliper; 376mm ventilated discs	
Steering	Rack-and-pinion; electromechanical	
DIMENSIONS		
Length (mm)	4,470	4,470
Width excl. mirrors (mm)	1,923	1,923
Height (mm)	1,314	1,311
Wheelbase (mm)	2,622	2,622
Track front/ rear (mm)	1,586/ 1,627	1,586/ 1,627
Kerbweight (kg)	From 1,650	From 1,665
Boot volume (litres)	315/ 407 with/without parcel tray and without Space Saver Spare	196.2 without Space Saver Spare
Fuel tank (usable) litres	70	70
PERFORMANCE & FUEL ECONOMY		
0-100km/h (sec)	4.2	4.2
Top speed mph (km/h)	300	300
Fuel consumption litres/100km EU combined	10.7	10.7
CO ₂ emissions (g/km) EU combined	255	255

Manufacturer's figures; correct at time of going to press

TECHNICAL DATA

	F-TYPE R AWD Coupé	F-TYPE R AWD Convertible
ENGINE & TRANSMISSION		
Engine capacity (cc)	5,000	
Cylinders	V8 Supercharged	
Valves per cylinder	4; DOHC	
Bore/ stroke (mm)	92.5/ 93.0	
Compression ratio	9.5:1	
Fuel injection	150bar direct injection	
Power kW	404 @ 6,500rpm	
Torque Nm	680 @ 3,500rpm	
Transmission	8-speed Quickshift	
Gear ratios (:1)		
1st	4.714	
2nd	3.143	
3rd	2.106	
4th	1.667	
5th	1.285	
6th	1.000	
7th	0.839	
8th	0.667	
Reverse	3.317	
Final Drive ratio	2.56	
CHASSIS		
Front suspension	Double wishbone	
Rear suspension	Double wishbone	
Front brakes	Twin-piston sliding caliper; 380mm ventilated discs	
Rear brakes	Single-piston sliding caliper; 376mm ventilated discs	
Steering	Rack-and-pinion; electromechanical	
DIMENSIONS		
Length (mm)	4,470	4,470
Width excl. mirrors (mm)	1,923	1,923
Height (mm)	1,314	1,311
Wheelbase (mm)	2,622	2,622
Track front/ rear (mm)	1,586/ 1,627	1,586/ 1,627
Kerbweight (kg)	From 1,730	From 1,745
Boot volume (litres)	315/ 407 with/without parcel tray and without Space Saver Spare	196.2 without Space Saver Spare
Fuel tank (usable) litres	70	70
PERFORMANCE & FUEL ECONOMY		
0-100km/h (sec)	4.1	4.1
Top speed mph (km/h)	300	300
Fuel consumption litres/100km EU combined	11.3	11.3
CO ₂ emissions (g/km) EU combined	269	269

Manufacturer's figures; correct at time of going to press